

Safety Data Sheet
MAPECOAT DW 25 comp.A

Safety Data Sheet dated: 14/06/2022 - version 4



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MAPECOAT DW 25 comp.A

Trade code: 901645

UFI: Y771-50P5-Y000-10AX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Epoxy paint

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI S.p.A. - Via Cafiero, 22 - 20158 Milano

Tel. +(39)02376731 (office hours) - Fax: +39-02-37673.214 - www.mapei.it

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

Centro antiveleni, Azienda ospedaliera "Antonio Cardarelli", III Servizio di anestesia e rianimazione, via Antonio Cardarelli 9, Napoli - Tel. 081 5453333

Centro antiveleni, Azienda ospedaliera universitaria Careggi, U.O. Tossicologia medica, via Largo Brambilla 3, Firenze - Tel. 055 7947819

Centro antiveleni, Centro nazionale d'informazione tossicologica, IRCCS Fondazione Salvatore Maugeri Clinica del lavoro e della riabilitazione, via Salvatore Maugeri 10, Pavia - Tel. 0382 24444

Centro antiveleni, Azienda ospedaliera Niguarda Ca' Granda, piazza Ospedale Maggiore 3, Milano - Tel. 02 66101029

Centro antiveleni, Azienda ospedaliera "Papa Giovanni XXIII", Tossicologia clinica, Dipartimento di farmacia clinica e farmacologia, piazza OMS 1, Bergamo - Tel. 800 883300

Centro antiveleni Policlinico "Umberto I", PRGM tossicologia d'urgenza, viale del Policlinico 155, Roma - Tel. 06 49978000

Centro antiveleni del Policlinico "Agostino Gemelli", Servizio di tossicologia clinica, largo Agostino Gemelli 8, Roma - Tel. 06 3054343

Centro antiveleni, Azienda ospedaliera universitaria Riuniti, viale Luigi Pinto 1, Foggia - Tel. 800 183459

Centro antiveleni, Ospedale pediatrico Bambino Gesù, Dipartimento emergenza e accettazione DEA, piazza Sant'Onofrio 4, Roma - Tel. 06 68593726

Centro antiveleni dell'Azienda ospedaliera universitaria integrata (AOUI) di Verona sede di Borgo Trento, piazzale Aristide Stefani, 1 - 37126 Verona - Tel. 800 011858

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 3	Flammable liquid and vapour.
Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
Skin Sens. 1	May cause an allergic skin reaction.
Aquatic Chronic 2	Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) n. 1272/2008 (CLP)

Pictograms and Signal Words



Warning

Hazard statements:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P280 Wear protective gloves/clothing and eye/face protection.
P370+P378 In case of fire, use a dry powder fire extinguisher to extinguish.
P391 Collect spillage.
P403+P235 Store in a well-ventilated place. Keep cool.

Special Provisions:

EUH205 Contains epoxy constituents. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This preparation contains low molecular weight epoxy resins. Cross sensitisation to other epoxies is possible. Avoid also exposure to spray mist and vapour.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not Relevant

3.2. Mixtures

Mixture identification: MAPECOAT DW 25 comp.A

Hazardous components within the meaning of the CLP regulation and related classification:

Concentration (% w/w)	Name	Ident. Numb.	Classification	Registration Number
≥50 - <75 %	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight <= 700)	CAS:1675-54-3, 25068-38-6, 25085-99-8 EC:216-823-5 Index:603-073-00-2	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Specific Concentration Limits: C ≥ 5%: Skin Irrit. 2 H315 C ≥ 5%: Eye Irrit. 2 H319	01-2119456619-26
≥5 - <10 %	ethanol; ethyl alcohol	CAS:64-17-5 EC:200-578-6 Index:603-002-00-5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Specific Concentration Limits: 50% ≤ C < 100%: Eye Irrit. 2 H319	01-2119457610-43-xxxx
≥0.1 - <0.25 %	free crystalline silica (Ø <10 µ)	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use a dry powder fire extinguisher to extinguish.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

	OEL Type	Country	Ceiling	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Note
ethanol; ethyl alcohol CAS: 64-17-5	DFG	GERMANY	C			1520	800	
	ACGIH						1000	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans; upper respiratory tract irritation;
	National	SWEDEN		1000	500			
	National	FRANCE		1900	1000	9500	5000	
	National	SPAIN				1910	1000	
	National	GREECE		1900	1000			
	National	DENMARK		1900	1000			
	National	FINLAND		1900	1000	2500	1300	
	National	GERMANY		960	500			
	National	PORTUGAL			1000			
	National	NORWAY		950	500	1187,5	625	
	National	BELGIUM		1907	1000			
	NDS	POLAND		1900				
	CHE	SWITZERLAND				1920	1000	
	NDS	NETHERLANDS		260		1900		
	National	CZECH REPUBLIC		1000				
	National	HUNGARY		1900		7600		
	Malaysi a OEL	MALAYSIA		1880	1000			
	National	ESTONIA		1000	500	1900	1000	
	National	LATVIA		1000				
	National	CZECH REPUBLIC	C			3000		
	National	SLOVAKIA	C			1920		
	National	SLOVAKIA		960	500			
	National	SLOVENIA		1900	1000	7600	4000	
	National	UNITED KINGDOM		1920	1000	5760	3000	
	National	BULGARIA		1000				
	National	ROMANIA		1900	1000	9500	5000	
	National	LITHUANIA		1000	500	1900	1000	
	National	CROATIA		1900	1000			
free crystalline silica (Ø <10 µ) CAS: 14808-60-7	National	SWEDEN		0,100				SWEDEN, respirable aerosol

National NORWAY	0,100		K: Chemicals to be treated as carcinogenic.
NDS POLAND	2,000		frakcja wdychalna
NDS POLAND	0,300		frakcja respirabilna
National DENMARK	0,3	0,600	DENMARK, inhalable aerosol inhalable aerosol
National DENMARK	0,100	0,200	DENMARK, respirable aerosol respirable aerosol
ACGIH	0,025		(R), A2 - Pulm fibrosis, lung cancer
EU	0,025		A2 (R) - Pulm fibrosis, lung cancer
National AUSTRIA	0,150		A*
ACGIH	0,025		A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
National SWEDEN	0,1		
National FRANCE	0,1		
National SPAIN	0,05		
National DENMARK	0,3		
National FINLAND	0,05		
National PORTUGAL	0,025		
National NORWAY	0,3	0,9	
National BELGIUM	0,1		
NDS POLAND	0,1		
NDS NETHERLANDS	0,075		
National CZECH REPUBLIC	0,1		
National HUNGARY	0,15		
Malaysi a OEL MALAYSIA	0,1		0.1 mg/m3 TWA (respirable dust)
National ESTONIA	0,1		
National SLOVAKIA	0,1	0,5	
National SLOVENIA	0,1		
National BULGARIA	0,07		
National ROMANIA	0,1		
National LITHUANIA	0,1		
National CROATIA	0,1		
National ITALY	0,100		

8.2. Exposure controls

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to appropriate EN standards, like EN 136, 140, 143, 149, 14387 for information on selection and use of appropriate respiratory protection equipment.

In case of insufficient ventilation use mask with ABEKP filters (EN 14387).

Hygienic and Technical measures

Not available

Appropriate engineering controls:

Not available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance: paste

Color: white

Odour: Characteristic

Odour threshold: Not available

Melting point / freezing point: Not available

Initial boiling point and boiling range: Not available

Flammability: The product is classified Flam. Liq. 3 H226

Upper/lower flammability or explosive limits: Not available

Flash point: 40 °C (104 °F)

Auto-ignition temperature: Not available

Decomposition temperature: Not available

pH: Not available

Viscosity: 5,000.00 cPs

Kinematic viscosity: Not available

Solubility in water: Insoluble

Solubility in oil: Not available

Partition coefficient (n-octanol/water): Not available

Vapour pressure: Not available

Relative density: 1.50 g/cm³

Vapour density: Not available

Particle characteristics:

Particle size: Not available

9.2. Other information

Miscibility: Not available

Conductivity: Not available

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the mixture:

- | | |
|--------------------------------------|--|
| a) acute toxicity | Not classified |
| | Based on available data, the classification criteria are not met |
| b) skin corrosion/irritation | The product is classified: Skin Irrit. 2(H315) |
| c) serious eye damage/irritation | The product is classified: Eye Irrit. 2(H319) |
| d) respiratory or skin sensitisation | The product is classified: Skin Sens. 1(H317) |
| e) germ cell mutagenicity | Not classified |
| | Based on available data, the classification criteria are not met |

f) carcinogenicity	Not classified	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

reaction product: a) acute toxicity LD50 Skin Rabbit = 20 mg/kg
 bisphenol-A-
 (epichlorhydrin); epoxy
 resin (number average
 molecular weight <= 700)

LD50 Oral Rat = 11300 µL/kg
 LD50 Skin Rabbit = 20000 mg/kg

ethanol; ethyl alcohol a) acute toxicity LC50 Inhalation Vapour Rat = mg/l 4h
 LD50 Oral Rat = 10470 mg/kg
 LD50 Skin Rat = 20000 mg/kg
 LD50 Oral Rat = 7060 mg/kg
 LC50 Inhalation Rat = 124,7 mg/l 4h

free crystalline silica (Ø <10 µ) a) acute toxicity LD50 Oral Rat = 500 mg/kg

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 2(H411)

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
ethanol; ethyl alcohol	CAS: 64-17-5 - EINECS: 200-578-6 - INDEX: 603-002-00-5	a) Aquatic acute toxicity : EC50 Daphnia > 10000 mg/L 48 a) Aquatic acute toxicity : LC50 Fish > 11200 mg/L 96 a) Aquatic acute toxicity : EC50 Algae > 200 mg/L 72 a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 12 mL/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas > 100 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 13400 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna 9268 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 2 mg/L 48h EPA

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

Not available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT RELATED MATERIAL (epoxy resins)

IATA-Technical name: PAINT RELATED MATERIAL (epoxy resins)

IMDG-Technical name: PAINT RELATED MATERIAL (epoxy resins)

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: III

IATA-Packing group: III

IMDG-Packing group: III

14.5. Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Yes

IMDG-EMS: F-E, S-E

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: 3

ADR-Hazard identification number: NA

ADR-Special Provisions: 163 367 650

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA) :

IATA-Passenger Aircraft: 355

IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea (IMDG) :

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 163 223 367 955

IMDG-EMS: F-E, S-E

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC) : 160 (A+B) g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) n. 2020/878

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1	Lower-tier threshold (tonnes)	Upper-tier threshold (tonnes)
Products belongs to category P5c	5000	50000
Products belongs to category E2	200	500

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 75

SVHC Substances:

SVHC substances not present in a concentration $\geq 0.1\%$ (w/w)

German Water Hazard Class (WGK)

Class 2: hazardous for water.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
---	--------------------------

2.6/3	On basis of test data
3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1	Calculation method
4.1/C2	Calculation method

If appropriate, specific provisions in relation to possible training for workers are mentioned in section 2. Any training related to safety in the workplace must in any case refer to a risk assessment that must be carried out by a company safety officer taking into account the specific operating and environmental conditions in which the products are used.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level.
DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: KAFH
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

*** Sheet model entirely changed in compliance to regulatory update.**